

How to use the psych package for mediation/moderation/regression analysis

William Revelle

January 4, 2022

Contents

1	Overview of this and related documents	3
1.1	Jump starting the <i>psych</i> package—a guide for the impatient	3
1.2	For the not impatient	4
2	Multiple regression and mediation	4
3	Regression using setCor	5
3.1	Comparison with <code>lm</code> on complete data	5
3.1.1	It is important to know your data by describing it first	5
3.1.2	Now do the regressions	5
3.2	From a correlation matrix	8
3.3	The Hotelling example	9
3.4	Moderated multiple regression	12
3.5	Plotting the interactions	13
3.6	Comparisons to <code>lm</code>	14
4	Mediation using the <code>mediate</code> function	16
4.1	Simple mediation	17
4.2	Multiple mediators	20
4.3	Serial mediators	21
4.4	Single mediators, multiple covariates	22
4.5	Single predictor, single criterion, multiple covariates	24
4.6	Multiple predictors, single criterion	25
5	Mediation and moderation	25
5.1	To center or not to center, that is the question	29

5.2	Another example of moderated mediation	32
5.3	Graphic Displays of Interactions	33
6	Partial Correlations	36
6.1	Partial some variables from the rest of the variables	36
6.2	Partial everything from everything	36
7	Related packages	37
8	Development version and a users guide	39
9	Psychometric Theory	39
10	SessionInfo	39

1 Overview of this and related documents

To do basic and advanced personality and psychological research using R is not as complicated as some think. This is one of a set of “How To” to do various things using R ([R Core Team, 2020](#)), particularly using the *psych* ([Revelle, 2020](#)) package.

The current list of How To’s includes:

1. An [introduction](#) (vignette) of the *psych* package
2. An [overview](#) (vignette) of the *psych* package
3. [Installing](#) R and some useful packages
4. Using R and the *psych* package to find ω_h and ω_t .
5. Using R and the *psych* for [factor analysis](#) and principal components analysis.
6. Using the `scoreItems` function to find [scale scores and scale statistics](#).
7. Using `mediate` and `setCor` to do [mediation, moderation and regression analysis](#) (this document)

1.1 Jump starting the *psych* package—a guide for the impatient

You have installed *psych* and you want to use it without reading much more. What should you do?

1. Activate the *psych* and *psychTools* packages.

```
> library(psych)
> library(psychTools)
```

R code

2. Input your data. If your file name ends in .sav, .text, .txt, .csv, .xpt, .rds, .Rds, .rda, or .RDATA, then just read it in directly using `read.file`. Or you can go to your friendly text editor or data manipulation program (e.g., Excel) and copy the data to the clipboard. Include a first line that has the variable labels. Paste it into *psych* using the `read.clipboard.tab` command:

```
myData <- read.file()      #this will open a search window on your machine
#                          and read or load the file.
#or
#first copy your file to your clipboard and then
myData <- read.clipboard.tab() #if you have an excel file
```

R code

3. Make sure that what you just read is right. Describe it and perhaps look at the first and last few lines. If you want to “view” the first and last few lines using a spreadsheet like viewer, use `quickView`.

```
describe(myData)
headTail(myData)
#or
quickView(myData)
```

R code

4. Look at the patterns in the data. If you have fewer than about 10 variables, look at the SPLOM (Scatter Plot Matrix) of the data using `pairs.panels`.

```
pairs.panels(myData)
```

R code

5. Find the correlations of all of your data.

- Descriptively (just the values)

```
lowerCor(myData)
```

R code

- Graphically

```
corPlot(myData) #does not show the values of the correlations
corPlot(myData, numbers=TRUE) #show the numbers,\
                             #scales the character size by "significance"
corPlot(myData, numbers=TRUE, scale=FALSE) #show the numbers,
                                           # all characters the same size
corPlot(lowerCor(myData), numbers =TRUE) #print the correlations
                                           # and show them graphically
```

R code

1.2 For the not impatient

The following pages are meant to lead you through the use of the `setCor` and `mediate` functions. The assumption is that you have already made *psych* active and want some example code.

2 Multiple regression and mediation

Mediation and moderation are merely different uses of the linear model $\hat{Y} = \mu + \beta_{y.x}X$ and are implemented in *psych* with two functions: `setCor` and `mediate`.

Given a set of predictor variables, X and a set of criteria variables, Y , multiple regression solves the equation $\hat{Y} = \mu + \beta_{y.x}X$ by finding $\beta_{y.x} = C_{xx}^{-1}C_{yx}$ where C_{xx} is the covariances of the X variables and C_{yx} is the covariances of predictors and the criteria.

Although typically done using the raw data, clearly this can also be done by using the covariance or correlation matrices. `setCor` was developed to handle the correlation matrix solution but has been generalized to the case of raw data. In the later case, it assumes a Missing Completely at Random (MCAR) structure, and thus uses all the data and finds pair.wise complete correlations. For complete data sets, the results are identical to using

`lm`. By default, `setCor` uses standardized variables, but to compare with `lm`, it can use unstandardized variables.

3 Regression using `setCor`

Although typically done from a raw data matrix (using the `lm` function), it is sometimes useful to do the regression from a correlation or covariance matrix. `setCor` was developed for this purpose. From a correlation/covariance matrix, it will do normal regression as well as regression on partialled correlation matrices. With the raw data, it will also do moderated regression (centered or non-centered). In particular, for the raw data, it will work with missing data.

An interesting option, if using categorical or dichotomous data is first find the appropriate polychoric, tetrachoric, or poly-serial correlations using `mixedCor` and then use the resulting correlation matrix for analysis. The resulting correlations and multiple correlations will not match those of the `lm` analysis.

3.1 Comparison with `lm` on complete data

We use the `attitude` data set for our first example.

3.1.1 It is important to know your data by describing it first

> `psych::describe(attitude)`
R code

	vars	n	mean	sd	median	trimmed	mad	min	max	range	skew	kurtosis	se
rating	1	30	64.63	12.17	65.5	65.21	10.38	40	85	45	-0.36	-0.77	2.22
complaints	2	30	66.60	13.31	65.0	67.08	14.83	37	90	53	-0.22	-0.68	2.43
privileges	3	30	53.13	12.24	51.5	52.75	10.38	30	83	53	0.38	-0.41	2.23
learning	4	30	56.37	11.74	56.5	56.58	14.83	34	75	41	-0.05	-1.22	2.14
raises	5	30	64.63	10.40	63.5	64.50	11.12	43	88	45	0.20	-0.60	1.90
critical	6	30	74.77	9.89	77.5	75.83	7.41	49	92	43	-0.87	0.17	1.81
advance	7	30	42.93	10.29	41.0	41.83	8.90	25	72	47	0.85	0.47	1.88

3.1.2 Now do the regressions

```
> #do not standardize
> mod1 <- setCor(rating ~ complaints + privileges, data=attitude,std=FALSE)
> mod1
```

R code

Call: `setCor(y = rating ~ complaints + privileges, data = attitude, std = FALSE)`

Multiple Regression from raw data

DV = rating	slope	se	t	p	lower.ci	upper.ci	VIF	Vy.x
(Intercept)	15.33	7.16	2.14	4.1e-02	0.64	30.02	1.00	0.00

complaints	0.78	0.12	6.54	5.2e-07	0.54	1.03	1.45	0.70
privileges	-0.05	0.13	-0.39	7.0e-01	-0.32	0.22	1.45	-0.02

Residual Standard Error = 7.1 with 27 degrees of freedom

Multiple Regression										
	R	R2	Ruw	R2uw	Shrunken R2	SE of R2	overall F	df1	df2	p
rating	0.83	0.68	0.62	0.38	0.66	0.08	29.1	2	27	1.83e-07

Compare this solution with the results of the `lm` function.

```
> summary(lm(rating ~ complaints + privileges, data=attitude))
```

Call:
lm(formula = rating ~ complaints + privileges, data = attitude)

Residuals:

Min	1Q	Median	3Q	Max
-12.7887	-5.6893	-0.0284	6.2745	9.9726

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	15.32762	7.16023	2.141	0.0415 *
complaints	0.78034	0.11939	6.536	5.22e-07 ***
privileges	-0.05016	0.12992	-0.386	0.7025

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 7.102 on 27 degrees of freedom
Multiple R-squared: 0.6831, Adjusted R-squared: 0.6596
F-statistic: 29.1 on 2 and 27 DF, p-value: 1.833e-07

The graphic for the standardized regression is shown in (Figure 1).

Call: `setCor(y = rating ~ complaints + privileges, data = attitude)`

Multiple Regression from raw data

DV = rating		slope	se	t	p	lower.ci	upper.ci	VIF	Vy.x
(Intercept)		0.00	0.11	0.00	1.0e+00	-0.22	0.22	1.00	0.00
complaints		0.85	0.13	6.54	5.2e-07	0.59	1.12	1.45	0.70
privileges		-0.05	0.13	-0.39	7.0e-01	-0.32	0.22	1.45	-0.02

Residual Standard Error = 0.58 with 27 degrees of freedom

Multiple Regression										
	R	R2	Ruw	R2uw	Shrunken R2	SE of R2	overall F	df1	df2	p
rating	0.83	0.68	0.71	0.5	0.66	0.08	29.1	2	27	1.83e-07

pdf
2

A simple regression model



Figure 1: A simple multiple regression using the attitude data set (standardized solution is shown).

3.2 From a correlation matrix

Perhaps most usefully, `setCor` will find the beta weights between a set of X variables, and a set of Y variables. Consider seven variables in the `attitude` data set. We first find the correlation matrix (normally, this could just be supplied by the user). Then we find the regressions from the correlation matrix. Compare this regression to the (standardized) solution shown above. By specifying the number of observations (`n.obs`), we are able to apply various inferential tests.

```
> R <- lowerCor(attitude)
```

R code

```
      ratng cmpln prvlg lrnng raiss crtcl advnc
rating      1.00
complaints  0.83  1.00
privileges  0.43  0.56  1.00
learning    0.62  0.60  0.49  1.00
raises      0.59  0.67  0.45  0.64  1.00
critical    0.16  0.19  0.15  0.12  0.38  1.00
advance     0.16  0.22  0.34  0.53  0.57  0.28  1.00
```

R code

```
> setCor(rating ~ complaints + privileges, data=R, n.obs = 30)
```

```
Call: setCor(y = rating ~ complaints + privileges, data = R, n.obs = 30)
```

Multiple Regression from matrix input

```
DV = rating
      slope   se      t      p lower.ci upper.ci VIF  Vy.x
complaints  0.85 0.13  6.54 5.2e-07    0.59    1.12 1.45  0.70
privileges -0.05 0.13 -0.39 7.0e-01   -0.32    0.22 1.45 -0.02
```

```
Residual Standard Error = 0.58 with 27 degrees of freedom
```

```
Multiple Regression
      R    R2  R2uw Shrunk R2 SE of R2 overall F df1 df2      p
rating 0.83 0.68 0.71  0.5    0.66   0.08   29.1  2  27 1.83e-07
```

Compare this solution (from the correlation matrix) with the *standardized* solution for the raw data. `setCor` does several things:

- Finds the regression weights (betas) between the predictor variables and each of the criterion variables.
- If the number of subjects is specified, or if the raw data are used, it also compares each of these betas to its standard error, finds a *t* statistic, and reports the probability of the $t > 0$.
- It reports the Multiple R and R^2 based upon these beta weights. In addition, following the tradition of the robust beauty of the improper linear models (Dawes, 1979) it also reports the unit weighted multiple correlations.
- The canonical correlations between the two sets (Hotelling, 1936) is reported.

- Cohen's set correlation (Cohen, 1982) as well as the unweighted correlation between the two sets of variables are reported.

3.3 The Hotelling example

```
> #the second Kelley data from Hotelling
> kelley <- structure(list(speed = c(1, 0.4248, 0.042, 0.0215, 0.0573), power = c(0.4248,
+ 1, 0.1487, 0.2489, 0.2843), words = c(0.042, 0.1487, 1, 0.6693,
+ 0.4662), symbols = c(0.0215, 0.2489, 0.6693, 1, 0.6915), meaningless = c(0.0573,
+ 0.2843, 0.4662, 0.6915, 1)), .Names = c("speed", "power", "words",
+ "symbols", "meaningless"), class = "data.frame", row.names = c("speed",
+ "power", "words", "symbols", "meaningless"))
> #first show the correlations
> lowerMat(kelley)
```

```

      speed power words symbol mnngl
speed      1.00
power      0.42  1.00
words      0.04  0.15  1.00
symbols    0.02  0.25  0.67  1.00
meaningless 0.06  0.28  0.47  0.69  1.00
```

```
> #now find and draw the regression
> sc <- setCor(power + speed ~ words + symbols + meaningless, data=kelley) #formula mode
> sc #show it
```

```
Call: setCor(y = power + speed ~ words + symbols + meaningless, data = kelley)
```

```
Multiple Regression from matrix input
```

```
DV = power
      slope VIF Vy.x
words    -0.03 1.81 -0.01
symbols    0.12 2.72  0.03
meaningless 0.22 1.92  0.06
```

```
Multiple Regression
      R  R2 Ruw R2uw
power 0.29 0.09 0.26 0.07
```

```
DV = speed
      slope VIF Vy.x
words     0.05 1.81  0
symbols   -0.07 2.72  0
meaningless 0.08 1.92  0
```

```
Multiple Regression
      R  R2 Ruw R2uw
speed 0.07 0.01 0.05  0
```

```
Various estimates of between set correlations
Squared Canonical Correlations
[1] 0.0946 0.0035
```

```
Average squared canonical correlation = 0.05
```

```

Cohen's Set Correlation R2 = 0.1
Unweighted correlation between the two sets = 0.18

```

A plot of the regression model is shown as well (Figure 2).

pdf
2




Figure 2: The relationship between three predictors and two criteria from `setCor`. The data are from the Kelley data set reported by [Hotelling \(1936\)](#).

But, we can also do multiple predictors *and* multiple criteria in the same call:

pdf
2

Regression Models




Figure 3: The relationship between three predictors and three criteria from `setCor`. The data are from the `sat.act` data set.

3.4 Moderated multiple regression

If we have the raw data, we can also find interactions (known as moderated multiple regression). This is done by zero centering the data (Cohen et al., 2003) and then multiplying the two terms of the interaction. As an option, we can not zero center the data (Hayes, 2013) which results in different “main effects” but the same interaction term. To show the equivalence of the interaction terms, we also must not standardize the results.

R code

```
> mod <- setCor(SATQ ~ SATV*gender + ACT, data=sat.act, std =FALSE, plot=FALSE)
> mod
```

```
Call: setCor(y = SATQ ~ SATV * gender + ACT, data = sat.act, std = FALSE,
  plot = FALSE)
```

Multiple Regression from raw data

```
DV = SATQ
      slope   se      t      p lower.ci upper.ci VIF Vy.x
(Intercept) -0.03 3.06 -0.01 9.9e-01   -6.03    5.98 1.00 0.00
SATV         0.47 0.03 14.47 1.1e-41    0.41    0.54 1.46 0.30
gender      -35.08 6.40 -5.48 6.0e-08   -47.66   -22.51 1.00 0.02
ACT          7.72 0.77 10.05 2.8e-22    6.22    9.23 1.47 0.19
SATV*gender  -0.03 0.06 -0.47 6.4e-01   -0.14    0.08 1.01 0.00
```

Residual Standard Error = 80.91 with 695 degrees of freedom

```
Multiple Regression
      R    R2  Ruw R2uw Shrunk R2 SE of R2 overall F df1 df2      p
SATQ 0.72 0.51 0.57 0.32      0.51    0.03   183.23  4 695 3.84e-107
```

R code

```
> mod0 <- setCor(SATQ ~ SATV*gender + ACT, data=sat.act, zero=FALSE, std=FALSE,plot=FALSE)
> mod0
```

```
Call: setCor(y = SATQ ~ SATV * gender + ACT, data = sat.act, std = FALSE,
  plot = FALSE, zero = FALSE)
```

Multiple Regression from raw data

```
DV = SATQ
      slope   se      t      p lower.ci upper.ci VIF Vy.x
(Intercept) 130.26 60.73  2.14 3.2e-02   11.02   249.50 1.00 0.00
SATV         0.52 0.10  5.20 2.7e-07    0.32    0.71 13.52 0.33
gender      -18.71 35.31 -0.53 6.0e-01   -88.03    50.61 30.44 0.01
ACT          7.72 0.77 10.05 2.8e-22    6.22    9.23 1.47 0.19
SATV*gender  -0.03 0.06 -0.47 6.4e-01   -0.14    0.08 41.50 -0.02
```

Residual Standard Error = 80.91 with 695 degrees of freedom

```
Multiple Regression
      R    R2  Ruw R2uw Shrunk R2 SE of R2 overall F df1 df2      p
SATQ 0.72 0.51 0.42 0.17      0.51    0.03   183.23  4 695 3.84e-107
```

pdf
2

pdf

Another example of moderated mediation





Figure 4: Showing a moderated multiple regression using `setCor`. The data are from the `sat.act` data set.

3.5 Plotting the interactions

To visualize the effect of zero (mean) centering, it is useful to plot the various elements that go into the linear model. `setCor` returns the product terms as well as the original data. I combine the two datasets to make it clearer. Note that the correlations of the centered SATQ, SATV, and gender with the uncentered are 1.0, but that the correlations with the product terms depend upon centering versus not. I drop the ACT variables from the figure for clarity (Figure 6).

pdf
2

Another example of moderated mediation



zero centered




Figure 5: The difference between 0 and not 0 centering `setCor`. The data are from the `sat.act` data set. In both cases, the data are not standardized.

3.6 Comparisons to `lm`

The `setCor` function duplicates the functionality of the `lm` function for complete data, although `lm` does not zero center and `setCor` will (by default). In addition, `setCor` finds correlations based upon pair.wise deletion of missing data, while `lm` does case.wise deletion. We compare the `lm` and `setCor` results for complete data by setting the `use = "complete"` option.

```
> lm(SATQ ~ SATV*gender + ACT, data=sat.act)
```

```
Call:
lm(formula = SATQ ~ SATV * gender + ACT, data = sat.act)
```

```
Coefficients:
(Intercept)      SATV      gender      ACT SATV:gender
  138.52395    0.50280   -22.24995    7.71702   -0.01984
```

```
> mod <- setCor(SATQ ~ SATV*gender + ACT, data=(sat.act), zero=FALSE, std=FALSE, use="complete")
> print(mod,digits=5)
```

```
Call: setCor(y = SATQ ~ SATV * gender + ACT, data = (sat.act), use = "complete",
std = FALSE, zero = FALSE)
```

Multiple Regression from raw data

```
DV = SATQ
      slope      se      t      p lower.ci upper.ci      VIF      Vy.x
(Intercept) 138.72572 60.61339 2.28870 2.2396e-02 19.71841 257.73303 1.00000 0.00000
```




Figure 6: The effect of not mean centering versus mean centering on the product terms. The first four variables were not zero centered, the second four were.

SATV	0.50280	0.09936	5.06050	5.3589e-07	0.30772	0.69788	13.43994	0.31739
gender	-22.24995	35.25783	-0.63106	5.2821e-01	-91.47457	46.97468	30.29663	0.01525
ACT	7.71702	0.76977	10.02511	3.4878e-22	6.20567	9.22837	1.46678	0.18928
SATV*gender	-0.01984	0.05652	-0.35105	7.2566e-01	-0.13082	0.09114	41.25607	-0.01191

Residual Standard Error = 81.18031 with 695 degrees of freedom

Multiple Regression

	R	R2	Ruw	R2uw	Shrunken R2	SE of R2	overall F	df1	df2	p
SATQ	0.71414	0.51	0.41706	0.17394	0.50718	0.02621	180.8401	4	695	3.93405e-106

4 Mediation using the mediate function

Mediation analysis is just linear regression reorganized slightly to show the direct effects of an X variable upon Y, partialling out the effect of a “mediator” (Figure 7). Although the statistical “significance” of the (c) path and the (c’) path are both available from standard regression, the mediation effect (ab) is best found by boot strapping the regression model and displaying the empirical confidence intervals.




Figure 7: The classic mediation model. The Direct Path from $X \rightarrow Y$ (c) is said to be mediated by the indirect path (a) to the mediator ($X \rightarrow M$) and (b) from the mediator to Y ($M \rightarrow Y$). The mediation effect is (ab).

A number of papers discuss how to test for the effect of mediation and there are some very popular ‘macros’ for SPSS and SAS to do so (Hayes, 2013; Preacher and Hayes, 2004; Preacher et al., 2007; Preacher, 2015). A useful discussion of mediation and moderation with sample data sets is found in Hayes (2013). More recently, the *processR* package (Moon, 2020) has been released with these data sets. Although these data used to be be

available from <http://www.afhayes.com/public/hayes2018data.zip> this now longer seems to be case.¹ I use these for comparisons with the results in Hayes (2013). Four of these data sets are now included in the *psych* package with the kind permission of their authors: Garcia is from Garcia et al. (2010), and Tal_Or is from Tal-Or et al. (2010), The Pollack correlation matrix is taken from an article by ?. The globalWarm data set is the glbwarm data set in the *processR* package and added to *psychTools* with the kind permission of the original author, Erik Nisbet.

To find the confidence intervals of the effect of mediation (the reduction between the c and c' paths, where $c' = c - ab$), I bootstrap the results by randomly sampling from the data with replacement ($n.iter = 5000$) times.

For these examples, the data files Garcia (Garcia et al., 2010) and Tal_Or (Tal-Or et al., 2010) are included in the *psych* package. The *estrss* data set and *glbwarm* were originally downloaded from the Hayes (2013) data set and stored in a local directory on my computer. They are now available from the *processR* package Moon (2020).

The syntax is that $y \sim x + (m)$ where m is the mediating variable. By default the output is to two decimals, as is the graphic output. This can be increased by returning the output to an object and then printing that object with the desired number of decimals.

4.1 Simple mediation

The first example (Hayes, 2013, mod.4.5) is taken from (Tal-Or et al., 2010) and examines the mediating effect of “Presumed Media Influence” (*pmi*) on the intention to act (*reaction*) based upon the importance of a message (*import*). The data are in the *Tal_Or* data set in *psych* (with the kind permission of Nurit Tal-Or, Jonanathan Cohen, Yariv Tasfati, and Albert Gunther). In the Hayes (2013) book, this is the *pmi* data set.

R code

```
> data(Tal.Or)
> psych::describe(Tal_Or) #descriptive statistics
```

	vars	n	mean	sd	median	trimmed	mad	min	max	range	skew	kurtosis	se
cond	1	123	0.47	0.50	0.00	0.46	0.00	0	1	1	0.11	-2.00	0.05
pmi	2	123	5.60	1.32	6.00	5.78	1.48	1	7	6	-1.17	1.30	0.12
import	3	123	4.20	1.74	4.00	4.26	1.48	1	7	6	-0.26	-0.89	0.16
reaction	4	123	3.48	1.55	3.25	3.44	1.85	1	7	6	0.21	-0.90	0.14
gender	5	123	1.65	0.48	2.00	1.69	0.00	1	2	1	-0.62	-1.62	0.04
age	6	123	24.63	5.80	24.00	23.76	1.48	18	61	43	4.71	24.76	0.52

R code

```
> mod4.4 <- mediate(reaction ~ cond + (pmi), data =Tal_Or)
> mod4.4
```

Mediation/Moderation Analysis

Call: `mediate(y = reaction ~ cond + (pmi), data = Tal_Or)`

¹The Hayes data sets (2018) do not correspond exactly with those from the 2013 book. Those data files were at <http://www.afhayes.com/public/hayes2013data.zip>.

The DV (Y) was reaction . The IV (X) was cond . The mediating variable(s) = pmi .

Total effect (c) of cond on reaction = 0.5 S.E. = 0.28 t = 1.79 df= 121 with p = 0.077
Direct effect (c') of cond on reaction removing pmi = 0.25 S.E. = 0.26 t = 0.99 df= 120 with p = 0.323
Indirect effect (ab) of cond on reaction through pmi = 0.24
Mean bootstrapped indirect effect = 0.24 with standard error = 0.13 Lower CI = 0.01 Upper CI = 0.51
R = 0.45 R2 = 0.21 F = 15.56 on 2 and 120 DF p-value: 1.31e-08

To see the longer output, specify short = FALSE in the print statement or ask for the summary

```
> #print(mod4.4, digits = 4) # in order to get the precision of the Hayes (2013) p 99 example
```

pdf
2




Figure 8: A simple mediation model (Hayes, 2013, p 99) with data derived from Tal-Or et al. (2010). The effect of a salience manipulation (cond) on the intention to buy a product (reaction) is mediated through the presumed media influence (pmi).

A second example from (Hayes, 2013) is an example of moderated mediated effect. The data are from (Garcia et al., 2010) and report on the effect of protest on reactions to a case of sexual discrimination.

R code

```
> data(GSBE) #alias to Garcia data set
> #compare two models (bootstrapping n.iter set to 50 for speed
> # 1) mean center the variables prior to taking product terms
> mod1 <- mediate(respappr ~ prot2 * sexism +(sexism),data=Garcia,n.iter=50
+ ,main="Moderated mediation (mean centered)")
> # 2) do not mean center
> mod2 <- mediate(respappr ~ prot2 * sexism +(sexism),data=Garcia,zero=FALSE, n.iter=50,
+ main="Moderated mediation (not centered)")
> summary(mod1)
```

```
Call: mediate(y = respappr ~ prot2 * sexism + (sexism), data = Garcia,
n.iter = 50, main = "Moderated mediation (mean centered)")
```

Direct effect estimates (traditional regression) (c') X + M on Y

	respappr	se	t	df	Prob
Intercept	-0.01	0.10	-0.12	125	9.07e-01
prot2	1.46	0.22	6.73	125	5.52e-10
prot2*sexism	0.81	0.28	2.87	125	4.78e-03
sexism	0.02	0.13	0.18	125	8.56e-01

R = 0.54 R2 = 0.3 F = 17.53 on 3 and 125 DF p-value: 1.46e-09

Total effect estimates (c) (X on Y)

	respappr	se	t	df	Prob
Intercept	-0.01	0.10	-0.12	126	9.06e-01
prot2	1.46	0.22	6.77	126	4.43e-10
prot2*sexism	0.81	0.28	2.89	126	4.49e-03

'a' effect estimates (X on M)

	sexism	se	t	df	Prob
Intercept	0.00	0.07	-0.02	126	0.986
prot2	0.07	0.15	0.47	126	0.642
prot2*sexism	0.09	0.19	0.44	126	0.661

'b' effect estimates (M on Y controlling for X)

	respappr	se	t	df	Prob
sexism	0.02	0.13	0.18	125	0.856

'ab' effect estimates (through mediators)

	respappr	boot	sd	lower	upper
prot2	0	0	0.02	-0.03	0.07
prot2*sexism	0	0	0.04	-0.08	0.09

Called from: summary.psych.mediate(object, digits = digits)

Compare the ab estimates for each mediator

	mean.diff	sd.diff	low	high
sexism*prot2*sexism x sexism*prot2	0	0.03	-0.07	0.05

R code

```
> summary(mod2)
```

```
Call: mediate(y = respappr ~ prot2 * sexism + (sexism), data = Garcia,
n.iter = 50, zero = FALSE, main = "Moderated mediation (not centered)")
```

```

Direct effect estimates (traditional regression)      (c') X + M on Y
      respappr se      t df      Prob
Intercept      6.57 1.21  5.43 125 2.83e-07
prot2          -2.69 1.45 -1.85 125 6.65e-02
prot2*sexism    0.81 0.28  2.87 125 4.78e-03
sexism         -0.53 0.24 -2.24 125 2.67e-02

R = 0.54 R2 = 0.3    F = 17.53 on 3 and 125 DF    p-value: 1.46e-09

Total effect estimates (c) (X on Y)
      respappr se      t df      Prob
Intercept      3.88 0.18 21.39 126 9.14e-44
prot2          0.00 0.84  0.00 126 9.96e-01
prot2*sexism    0.28 0.16  1.79 126 7.56e-02

'a' effect estimates (X on M)
      sexism se      t df      Prob
Intercept      5.07 0.07 75.12 126 1.69e-106
prot2          -5.07 0.31 -16.33 126 6.81e-33
prot2*sexism    1.00 0.06 17.15 126 9.41e-35

'b' effect estimates (M on Y controlling for X)
      respappr se      t df      Prob
sexism         -0.53 0.24 -2.24 125 0.0267

'ab' effect estimates (through mediators)
      respappr boot sd lower upper
prot2          2.68 2.85 1.61 -0.30 5.60
prot2*sexism   -0.53 -0.56 0.32 -1.11 0.06
Called from: summary.psych.mediate(object, digits = digits)

Compare the ab estimates for each mediator
      mean.diff sd.diff low high
sexism*prot2*sexism x sexism*prot2    -3.41    1.92 -6.71 0.36

```

4.2 Multiple mediators

It is trivial to show the effect of multiple mediators. I do this by adding the second (or third) mediator into our equation. I use the `Tal_Or` data set (Tal-Or et al., 2010) again. I show the graphical representation in Figure 9.

```

R code
> mod5.4 <- mediate(reaction ~ cond + (import) + (pmi), data = Tal_Or)
> print(mod5.4, digits=4) #to compare with Hayes

```

Mediation/Moderation Analysis

```
Call: mediate(y = reaction ~ cond + (import) + (pmi), data = Tal_Or)
```

```
The DV (Y) was reaction . The IV (X) was cond . The mediating variable(s) = import pmi .
```

```

Total effect (c) of cond on reaction = 0.4957 S.E. = 0.2775 t = 1.786 df= 121 with p = 0.0766
Direct effect (c') of cond on reaction removing import pmi = 0.1034 S.E. = 0.2391 t = 0.4324 d
Indirect effect (ab) of cond on reaction through import pmi = 0.3923
Mean bootstrapped indirect effect = 0.206 with standard error = 0.1147 Lower CI = 0.0112 Upper CI =
R = 0.5702 R2 = 0.3251 F = 19.1118 on 3 and 119 DF p-value: 3.6636e-12

```

To see the longer output, specify `short = FALSE` in the print statement or ask for the summary

>


pdf
2**Hayes example 5.3**

Figure 9: A mediation model with two mediators (Hayes, 2013, p 131). The data are data derived from Tal-Or et al. (2010). The effect of a salience manipulation (cond) on the intention to buy a product (reaction) is mediated through the presumed media influence (pmi) and importance of the message (import).

4.3 Serial mediators

The example from Hayes (2013) for two mediators, where one effects the second, is a bit more complicated and currently can be done by combining two separate analyses. The first is just model 5.4, the second is the effect of cond on pmi mediated by import.

Combining the two results leads to the output found on ([Hayes, 2013](#), page 153).

pdf
2

R code

```
> #model 5.4 + mod5.7 is the two chained mediator model
> mod5.7 <- mediate(pmi ~ cond + (import) , data = Tal_Or)
> summary(mod5.7, digits=4)
```

Call: mediate(y = pmi ~ cond + (import), data = Tal_Or)

Direct effect estimates (traditional regression) (c') X + M on Y

	pmi	se	t	df	Prob
Intercept	4.6104	0.3057	15.0836	120	1.7543e-29
cond	0.3536	0.2325	1.5207	120	1.3096e-01
import	0.1961	0.0671	2.9228	120	4.1467e-03

R = 0.3114 R2 = 0.097 F = 6.4428 on 2 and 120 DF p-value: 0.0021989

Total effect estimates (c) (X on Y)

	pmi	se	t	df	Prob
Intercept	5.3769	0.1618	33.2222	121	1.1593e-62
cond	0.4765	0.2357	2.0218	121	4.5401e-02

'a' effect estimates (X on M)

	import	se	t	df	Prob
Intercept	3.9077	0.2127	18.3704	121	8.3936e-37
cond	0.6268	0.3098	2.0234	121	4.5235e-02

'b' effect estimates (M on Y controlling for X)

	pmi	se	t	df	Prob
import	0.1961	0.0671	2.9228	120	0.0041467

'ab' effect estimates (through mediators)

	pmi	boot	sd	lower	upper
cond	0.1229	0.1245	0.0856	-0.0014	0.3334

Called from: summary.psych.mediate(object, digits = digits)

4.4 Single mediators, multiple covariates

The Pollack data set ([Pollack et al., 2012](#)) is used as an example of multiple covariates (included in *psychTools* as a correlation matrix). The raw data are available from the *processR* package as *estress*. Confidence in executive decision making ("Entrepreneurial self-efficacy"), gender (sex), and length of time in business (tenure) are used as covariates. There are two ways of doing this: enter them as predictors of the criterion or to partial them out. The first approach estimates their effects, the second just removes them.

R code

```
> lowerMat(Pollack)
```

	sex	age	tenur	slf.f	cmptn	scl.t	ecnm.	dprss	wthdr
sex	1.00								
age	0.07	1.00							
tenure	0.03	0.32	1.00						
self.efficacy	-0.02	-0.09	-0.06	1.00					

competence	0.08	0.01	0.02	0.22	1.00		
social.ties	0.07	-0.06	0.01	0.19	0.13	1.00	
economic.stress	-0.15	0.09	0.07	-0.16	-0.09	-0.07	1.00
depression	-0.05	-0.02	-0.07	-0.25	0.06	-0.05	0.34 1.00
withdrawal	-0.03	-0.05	-0.04	-0.24	-0.09	-0.01	0.06 0.42 1.00

R code

```
> mod6.2 <- mediate(withdrawal ~ economic.stress + self.efficacy + sex + tenure + (depression),
+ data=Pollack, n.obs=262)
> summary(mod6.2)
```

Call: mediate(y = withdrawal ~ economic.stress + self.efficacy + sex + tenure + (depression), data = Pollack, n.obs = 262)

Direct effect estimates (traditional regression) (c') X + M on Y

	withdrawal	se	t	df	Prob
Intercept	0.00	0.06	0.00	256	1.00e+00
economic.stress	-0.11	0.06	-1.82	256	6.99e-02
self.efficacy	-0.15	0.06	-2.67	256	8.01e-03
sex	-0.03	0.06	-0.50	256	6.15e-01
tenure	-0.01	0.06	-0.21	256	8.37e-01
depression	0.42	0.06	6.83	256	6.05e-11

R = 0.45 R2 = 0.21 F = 13.35 on 5 and 256 DF p-value: 1.45e-11

Total effect estimates (c) (X on Y)

	withdrawal	se	t	df	Prob
Intercept	0.00	0.06	0.00	257	1.000000
economic.stress	0.02	0.06	0.34	257	0.737000
self.efficacy	-0.24	0.06	-3.92	257	0.000113
sex	-0.03	0.06	-0.49	257	0.624000
tenure	-0.05	0.06	-0.91	257	0.366000

'a' effect estimates (X on M)

	depression	se	t	df	Prob
Intercept	0.00	0.06	0.00	257	1.00e+00
economic.stress	0.31	0.06	5.36	257	1.88e-07
self.efficacy	-0.21	0.06	-3.56	257	4.36e-04
sex	0.00	0.06	-0.07	257	9.46e-01
tenure	-0.10	0.06	-1.82	257	6.98e-02

'b' effect estimates (M on Y controlling for X)

	withdrawal	se	t	df	Prob
depression	0.42	0.06	6.83	256	6.05e-11

'ab' effect estimates (through mediators)

	withdrawal	boot	sd	lower	upper
economic.stress	0.13	0.13	0.03	0.08	0.19
self.efficacy	-0.09	-0.09	0.03	-0.16	-0.04
sex	0.00	-0.01	0.03	-0.07	0.04
tenure	-0.04	-0.05	0.03	-0.10	0.00

Called from: summary.psych.mediate(object, digits = digits)

Compare the ab estimates for each mediator

	mean.diff	sd.diff	low	high
depression*self.efficacy x depression*economic.stress	-0.23	0.04	-0.32	-0.15
depression*sex x depression*economic.stress	-0.15	0.04	-0.23	-0.07
depression*sex x depression*self.efficacy	0.08	0.04	0.01	0.15
depression*tenure x depression*economic.stress	-0.18	0.04	-0.27	-0.10

depression*tenure x depression*self.efficacy	0.05	0.03	-0.02	0.11
depression*tenure x depression*sex	-0.03	0.04	-0.11	0.05

pdf
2

The graphical output (Figure 10) looks a bit more complicated than the figure in (Hayes, 2013, p 177) because I am showing the covariates as causal paths.




Figure 10: A mediation model with three covariates (Hayes, 2013, p 177). Compare this to the solution in which they are partialled out. (Figure 11).

4.5 Single predictor, single criterion, multiple covariates

An alternative way to display the previous results is to remove the three covariates from the mediation model. I do this by partialling out the covariates. This is represented in the

mediate code by a negative sign. (Figure 11)

```

R code
> mod6.2a <- mediate(withdrawal ~ economic.stress -self.efficacy - sex - tenure + (depression),
+ data=Pollack, n.obs=262)
> summary(mod6.2a)

Call: mediate(y = withdrawal ~ economic.stress - self.efficacy - sex -
  tenure + (depression), data = Pollack, n.obs = 262)

Direct effect estimates (traditional regression)      (c') X + M on Y
      withdrawal*   se      t   df   Prob
Intercept           0.00 0.06  0.00 256 1.00e+00
economic.stress     -0.11 0.06 -1.80 256 7.23e-02
depression           0.42 0.06  6.78 256 8.50e-11

R = 0.39 R2 = 0.15   F = 23.41 on 2 and 256 DF   p-value: 4.6e-10

Total effect estimates (c) (X on Y)
      withdrawal*   se      t   df   Prob
Intercept           0.00 0.06  0.00 257 1.000
economic.stress      0.02 0.06  0.34 257 0.737

'a' effect estimates (X on M)
      depression   se      t   df   Prob
Intercept          0.00 0.06  0.00 257 1.00e+00
economic.stress     0.31 0.06  5.36 257 1.88e-07

'b' effect estimates (M on Y controlling for X)
      withdrawal*   se      t   df   Prob
depression          0.42 0.06  6.83 256 6.05e-11

'ab' effect estimates (through mediators)
      withdrawal* boot   sd lower upper
economic.stress     0.13 0.17 0.03  0.11  0.24
Called from: summary.psych.mediate(object, digits = digits)

pdf
2

```

4.6 Multiple predictors, single criterion

It is straightforward to use multiple predictors see (Hayes, 2013, p196) and in fact I did so in the previous example where the predictors were treated as *covariates*. `mediate` also allows for multiple criteria.

5 Mediation and moderation

We already saw how to do moderation in the discussion of `setCor`. Combining the concepts of mediation with moderation is done in `mediate`. That is, I can find the linear model of product terms as they are associated with dependent variables and regressed on the mediating variables.

Simple mediation, 3 covariates (partialled out)




Figure 11: Show the mediation model from Figure 10 with the covariates (ese, sex, tenure) removed.

The Garcia data set (Garcia et al., 2010) can be used for an example of moderation. (This was taken from (Hayes, 2013) but is used with kind permission of Donna M. Garcia, Michael T. Schmitt, Nyla R. Branscombe, and Naomi Ellemers.) Just as `setCor` and `lm` will find the interaction term by forming a product, so will `mediate`. Notice that by default, `setCor` reports zero centered and standardized regressions, `mediate` reports zero centered but not standardized regressions, and some of the examples from Hayes (2013) do not zero center the data. Thus, I specify `zero=FALSE` to get the Hayes (2013) results.

It is important to note that the `protest` data set discussed here is from the 2013 examples and not the more recent 2018 examples available from afhayes.com. The 2013 data have a dichotomous protest variable, while the 2018 data set has three levels for the protest variable. The Garcia data set is composed of the 2018 data set with the addition of a dichotomous variable (`prot2`) to match the 2013 examples.

We consider how the interaction of sexism with protest affects the mediation effect of sexism (Hayes, 2013, p 362), I contrast the `lm`, `setCor` and `mediate` approaches. For reasons to be discussed in the next section, I do not zero center the variables. The graphic output is in Figure 12 and the output is below. For comparison purposes, I show the results from the `lm` as well as `setCor` and `mediate`.

```
> summary(lm(respappr ~ prot2 * sexism,data = Garcia)) #show the lm results for comparison
```

```
Call:
lm(formula = respappr ~ prot2 * sexism, data = Garcia)

Residuals:
    Min       1Q   Median       3Q      Max
-3.4984 -0.7540  0.0801  0.8301  3.1853

Coefficients:
            Estimate Std. Error t value Pr(>|t|)
(Intercept)   6.5667     1.2095   5.429 2.83e-07 ***
prot2         -2.6866     1.4515  -1.851  0.06654 .
sexism         -0.5290     0.2359  -2.243  0.02668 *
prot2:sexism    0.8100     0.2819   2.873  0.00478 **
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 1.144 on 125 degrees of freedom
Multiple R-squared:  0.2962,    Adjusted R-squared:  0.2793
F-statistic: 17.53 on 3 and 125 DF,  p-value: 1.456e-09
```

```
> #show the setCor analysis
> setCor(respappr ~ prot2* sexism ,data=Garcia,zero=FALSE,main="Moderation",std=FALSE)
```

```
Call: setCor(y = respappr ~ prot2 * sexism, data = Garcia, std = FALSE,
  main = "Moderation", zero = FALSE)
```

```
Multiple Regression from raw data
```

```
DV = respappr
```

	slope	se	t	p	lower.ci	upper.ci	VIF	Vy.x
(Intercept)	6.57	1.21	5.43	2.8e-07	4.17	8.96	1.00	0.00
prot2	-2.69	1.45	-1.85	6.7e-02	-5.56	0.19	44.99	-0.47
sexism	-0.53	0.24	-2.24	2.7e-02	-1.00	-0.06	3.34	-0.01
prot2*sexism	0.81	0.28	2.87	4.8e-03	0.25	1.37	48.14	0.77

Residual Standard Error = 1.14 with 125 degrees of freedom

Multiple Regression

	R	R2	Ruw	R2uw	Shrunken R2	SE of R2	overall F	df1	df2	p
respappr	0.54	0.3	0.41	0.17	0.28	0.06	17.53	3	125	1.46e-09

R code

```
> #then show the mediate results
>
> modgarcia <-mediate(respappr ~ prot2 * sexism +(sexism),data=Garcia,zero=FALSE,main="Moderated mediation")
> summary(modgarcia)
```

Call: mediate(y = respappr ~ prot2 * sexism + (sexism), data = Garcia,
zero = FALSE, main = "Moderated mediation")

Direct effect estimates (traditional regression) (c') X + M on Y

	respappr	se	t	df	Prob
Intercept	6.57	1.21	5.43	125	2.83e-07
prot2	-2.69	1.45	-1.85	125	6.65e-02
prot2*sexism	0.81	0.28	2.87	125	4.78e-03
sexism	-0.53	0.24	-2.24	125	2.67e-02

R = 0.54 R2 = 0.3 F = 17.53 on 3 and 125 DF p-value: 1.46e-09

Total effect estimates (c) (X on Y)

	respappr	se	t	df	Prob
Intercept	3.88	0.18	21.39	126	9.14e-44
prot2	0.00	0.84	0.00	126	9.96e-01
prot2*sexism	0.28	0.16	1.79	126	7.56e-02

'a' effect estimates (X on M)

	sexism	se	t	df	Prob
Intercept	5.07	0.07	75.12	126	1.69e-106
prot2	-5.07	0.31	-16.33	126	6.81e-33
prot2*sexism	1.00	0.06	17.15	126	9.41e-35

'b' effect estimates (M on Y controlling for X)

	respappr	se	t	df	Prob
sexism	-0.53	0.24	-2.24	125	0.0267

'ab' effect estimates (through mediators)

	respappr	boot	sd	lower	upper
prot2	2.68	2.67	1.62	-0.67	5.70
prot2*sexism	-0.53	-0.53	0.32	-1.12	0.13


Called from: summary.psych.mediate(object, digits = digits)

Compare the ab estimates for each mediator

	mean.diff	sd.diff	low	high
sexism*prot2*sexism x sexism*prot2	-3.19	1.94	-6.83	0.8

R code

```
>
```



5.1 To center or not to center, that is the question

With the global warming data from [Hayes \(2013\)](#), the default (uncentered) regression does not reproduce his Table, but zero centering does. To this in `lm` requires two steps, but we can do this in `setCor` with the `zero=TRUE` or `zero=FALSE` option.

```

R code
> lm(govact ~ age * negemot + posemot + ideology + sex, data=globalWarm)

```

```

Call:
lm(formula = govact ~ age * negemot + posemot + ideology + sex,
    data = globalWarm)

```

```

Coefficients:
(Intercept)      age      negemot      posemot      ideology      sex  age:negemot
  5.173849   -0.023879   0.119583   -0.021419   -0.211515   -0.011191   0.006331

```

```

R code
> # but zero center and try again
> glbwarmc <- data.frame(scale(globalWarm, scale=FALSE))
> lm(govact ~ age * negemot + posemot + ideology + sex, data=glbwarmc)

```

```

Call:
lm(formula = govact ~ age * negemot + posemot + ideology + sex,
    data = glbwarmc)

```

```

Coefficients:
(Intercept)      age      negemot      posemot      ideology      sex  age:negemot
  0.008979   -0.001354   0.433184   -0.021419   -0.211515   -0.011191   0.006331

```

```

R code
> mod.glb <- setCor(govact ~ age * negemot + posemot + ideology + sex, data=globalWarm, zero=FALSE, std=FALSE)
> print(mod.glb, digits=6)

```

```

Call: setCor(y = govact ~ age * negemot + posemot + ideology + sex,
             data = globalWarm, std = FALSE, zero = FALSE)

```

Multiple Regression from raw data

```

DV = govact

```

	slope	se	t	p	lower.ci	upper.ci	VIF	Vy.x
(Intercept)	5.173849	0.338451	15.286838	1.58157e-46	4.509502	5.838197	1.000000	0.000000
age	-0.023879	0.005980	-3.992944	7.12038e-05	-0.035618	-0.012140	6.949401	0.027844
negemot	0.119583	0.082535	1.448881	1.47759e-01	-0.042425	0.281591	11.594520	0.077620
posemot	-0.021419	0.027904	-0.767597	4.42951e-01	-0.076193	0.033354	1.028663	-0.000912
ideology	-0.211515	0.026833	-7.882678	1.03603e-14	-0.264185	-0.158845	1.198910	0.098323
sex	-0.011191	0.076003	-0.147240	8.82979e-01	-0.160378	0.137997	1.052907	0.000406
age*negemot	0.006331	0.001543	4.103542	4.48155e-05	0.003302	0.009359	16.455422	0.197526

Residual Standard Error = 1.056984 with 808 degrees of freedom

```

Multiple Regression

```

	R	R2	Ruw	R2uw	Shrunken R2	SE of R2	overall F	df1	df2	p
govact	0.633093	0.400806	0.14033	0.019693	0.396357	0.026299	90.07983	6	808	1.824604e-86

```

R code
> mod.glb0 <- setCor(govact ~ age * negemot + posemot + ideology + sex, data=globalWarm, std=FALSE)
> print(mod.glb0, digits=6)

```

```

Call: setCor(y = govact ~ age * negemot + posemot + ideology + sex,
             data = globalWarm, std = FALSE)

```

Multiple Regression from raw data

```

DV = govact

```

	slope	se	t	p	lower.ci	upper.ci	VIF	Vy.x
--	-------	----	---	---	----------	----------	-----	------

```

(Intercept)  0.008979 0.037089  0.242103 8.08762e-01 -0.063823  0.081782 1.000000  0.000000
age          -0.001354 0.002348 -0.576864 5.64192e-01 -0.005963  0.003254 1.071058  0.001579
negemot      0.433184 0.026243 16.506679 5.75775e-53  0.381671  0.484696 1.172207  0.281175
posemot     -0.021419 0.027904 -0.767597 4.42951e-01 -0.076193  0.033354 1.028663 -0.000912
ideology    -0.211515 0.026833 -7.882678 1.03603e-14 -0.264185 -0.158845 1.198910  0.098323
sex         -0.011191 0.076003 -0.147240 8.82979e-01 -0.160378  0.137997 1.052907  0.000406
age*negemot  0.006331 0.001543  4.103542 4.48155e-05  0.003302  0.009359 1.014744  0.020236

```

Residual Standard Error = 1.056984 with 808 degrees of freedom

```

Multiple Regression
      R      R2      Ruw      R2uw Shrunk R2 SE of R2 overall F df1 df2      p
govact 0.633093 0.400806 0.458776 0.210475  0.396357 0.026299 90.07983  6 808 1.824604e-86

```

So, when we do the mediated moderation model, we need to use the zero centered option to match the [Hayes \(2013\)](#) results from Figure 8.5.

```

R code
> #by default, mediate zero centers before finding the products
> mod.glb <- mediate(govact ~ age * negemot + posemot + ideology + sex + (age), data=globalWarm, zero=TRUE)
> summary(mod.glb, digits=4)

```

```

Call: mediate(y = govact ~ age * negemot + posemot + ideology + sex +
  (age), data = globalWarm, zero = TRUE)

```

```

Direct effect estimates (traditional regression)      (c') X + M on Y
      govact      se      t      df      Prob
Intercept  0.0090 0.0371  0.2421 808 8.0876e-01
negemot     0.4332 0.0262 16.5067 808 5.7578e-53
posemot    -0.0214 0.0279 -0.7676 808 4.4295e-01
ideology   -0.2115 0.0268 -7.8827 808 1.0360e-14
sex        -0.0112 0.0760 -0.1472 808 8.8298e-01
age*negemot 0.0063 0.0015  4.1035 808 4.4816e-05
age        -0.0014 0.0023 -0.5769 808 5.6419e-01

```

R = 0.6331 R2 = 0.4008 F = 90.0798 on 6 and 808 DF p-value: 1.8246e-86

```

Total effect estimates (c) (X on Y)
      govact      se      t      df      Prob
Intercept  0.0090 0.0371  0.2420 809 8.0881e-01
negemot     0.4328 0.0262 16.5043 809 5.8181e-53
posemot    -0.0220 0.0279 -0.7890 809 4.3036e-01
ideology   -0.2145 0.0263 -8.1510 809 1.3690e-15
sex        -0.0173 0.0752 -0.2304 809 8.1783e-01
age*negemot 0.0063 0.0015  4.1025 809 4.4999e-05

```

```

'a' effect estimates (X on M)
      age      se      t      df      Prob
Intercept  0.0044 0.5554  0.0079 809 9.9366e-01
negemot     0.2757 0.3929  0.7017 809 4.8305e-01
posemot     0.4232 0.4176  1.0135 809 3.1112e-01
ideology    2.2079 0.3943  5.6002 809 2.9334e-08
sex         4.5345 1.1269  4.0238 809 6.2643e-05
age*negemot 0.0031 0.0231  0.1346 809 8.9294e-01

```

```

'b' effect estimates (M on Y controlling for X)
      govact      se      t      df      Prob
age -0.0014 0.0023 -0.5769 808 0.56419

```

```

'ab' effect estimates (through mediators)
      govact    boot      sd    lower    upper
negemot    -0.0004  0.0000  0.0001 -0.0002  0.0002
posemot    -0.0006 -0.0005  0.0014 -0.0042  0.0020
ideology    -0.0030 -0.0028  0.0052 -0.0137  0.0072
sex         -0.0061 -0.0056  0.0107 -0.0278  0.0152
age*negemot 0.0000  0.0000  0.0001 -0.0002  0.0002
Called from: summary.psych.mEDIATE(object, digits = digits)

```

```

Compare the ab estimates for each mediator
      mean.diff sd.diff      low      high
age*posemot x age*negemot    -0.0005  0.0014 -0.0041  0.0020
age*ideology x age*negemot   -0.0028  0.0052 -0.0136  0.0072
age*ideology x age*posemot   -0.0023  0.0044 -0.0118  0.0062
age*sex x age*negemot        -0.0056  0.0106 -0.0279  0.0152
age*sex x age*posemot        -0.0051  0.0099 -0.0264  0.0139
age*sex x age*ideology        -0.0028  0.0062 -0.0170  0.0086
age*age*negemot x age*negemot 0.0000  0.0000  0.0000  0.0000
age*age*negemot x age*posemot 0.0005  0.0014 -0.0020  0.0041
age*age*negemot x age*ideology 0.0028  0.0052 -0.0072  0.0136
age*age*negemot x age*sex      0.0056  0.0106 -0.0152  0.0279

```

Compare this output to that of Table 8.2 and Figure 8.5 (p 258 - 259).

5.2 Another example of moderated mediation

The Garcia data set (protest in [Hayes \(2013\)](#)) is another example of a moderated analysis. We can use either `setCor` or `mediate` to examine this data set. The defaults for these two differ, in that `setCor` assumes we want to zero center *and* standardize, while `mediate` defaults to not standardizing but also defaults to zero (mean) centering. Note that in the next examples we specify we do not want to standardize nor to mean center.

```

> psych::describe(Garcia)
R code

```

	vars	n	mean	sd	median	trimmed	mad	min	max	range	skew	kurtosis	se
protest	1	129	1.03	0.82	1.00	1.04	1.48	0.00	2	2.00	-0.06	-1.52	0.07
sexism	2	129	5.12	0.78	5.12	5.10	0.74	2.87	7	4.13	0.12	-0.32	0.07
anger	3	129	2.12	1.66	1.00	1.84	0.00	1.00	7	6.00	1.29	0.26	0.15
liking	4	129	5.64	1.05	5.83	5.73	0.99	1.00	7	6.00	-1.15	2.48	0.09
respappr	5	129	4.87	1.35	5.25	4.98	1.11	1.50	7	5.50	-0.75	-0.18	0.12
prot2	6	129	0.68	0.47	1.00	0.72	0.00	0.00	1	1.00	-0.77	-1.41	0.04

```

R code
> lm(liking ~ prot2* sexism + respappr, data=Garcia)

```

```

Call:
lm(formula = liking ~ prot2 * sexism + respappr, data = Garcia)

```

```

Coefficients:
(Intercept)      prot2      sexism      respappr  prot2:sexism
  5.3471      -2.8075      -0.2824      0.3593      0.5426

```

```

R code
> setCor(liking ~ prot2* sexism + respappr, data = Garcia, zero=FALSE, std=FALSE)

```



```
Call: setCor(y = liking ~ prot2 * sexism + respappr, data = Garcia,
  std = FALSE, zero = FALSE)
```

Multiple Regression from raw data

```
DV = liking
      slope  se      t      p lower.ci upper.ci  VIF  Vy.x
(Intercept)  5.35 1.06  5.04 1.6e-06   3.25    7.45  1.00  0.00
prot2        -2.81 1.16 -2.42 1.7e-02  -5.10   -0.51 46.22 -0.27
sexism        -0.28 0.19 -1.49 1.4e-01  -0.66    0.09  3.47 -0.02
respappr       0.36 0.07  5.09 1.3e-06   0.22    0.50  1.42  0.23
prot2*sexism   0.54 0.23  2.36 2.0e-02   0.09    1.00 51.32  0.34
```

Residual Standard Error = 0.9 with 124 degrees of freedom

```
Multiple Regression
      R    R2  Ruw R2uw Shrunken R2 SE of R2 overall F df1 df2      p
liking 0.53 0.28 0.34 0.12      0.26    0.06    12.26   4 124 1.99e-08
```

```
> mod7.4 <- mediate(liking ~ prot2 * sexism + respappr, data = Garcia, zero=FALSE)
> summary(mod7.4)
```

```
Call: mediate(y = liking ~ prot2 * sexism + respappr, data = Garcia,
  zero = FALSE)
```

No mediator specified leads to traditional regression

```
      liking  se      t  df      Prob
Intercept    5.35 1.06  5.04 124 1.60e-06
prot2        -2.81 1.16 -2.42 124 1.70e-02
sexism        -0.28 0.19 -1.49 124 1.39e-01
respappr       0.36 0.07  5.09 124 1.28e-06
prot2*sexism   0.54 0.23  2.36 124 1.97e-02
```

R = 0.53 R2 = 0.28 F = 12.26 on 4 and 124 DF p-value: 1.99e-08

pdf
2

5.3 Graphic Displays of Interactions

In order to graphically display interactions, particularly if one of the variable is categorical, we can plot separate regression lines for each value of the categorical variable. We do this for the Garcia data set to show the interaction of protest with sexism. (see Figure 14). This is just an example of how to use Core-R to do graphics and is not a feature of *psych*.

```
Garcia$protest: 0
NULL
```

```
Garcia$protest: 1
NULL
```

```
Garcia$protest: 2
NULL
```

pdf
2

Another example of moderated mediation




Figure 13: A simple moderated regression analysis of the **protest** data set. The data were not zero centered. This shows the strength of the three regressions. Figure 14 shows the actual data and the three regression lines.




Figure 14: Showing the interaction between type of protest and sexism from the Garcia data set. The strength of the regression effects is shown in Fig 13.

6 Partial Correlations

Although not strickly speaking part of mediation or moderation, the use of *partial correlations* can be addressed here.

6.1 Partial some variables from the rest of the variables

Given a set of X variables and a set of Y variables, we can control for an additional set of Z variables when we find the correlations between X and Y. This is effectively what happens when we want to add covariates into a model. We see this when we compare the regression model for government action as a function of the interaction of ideology and age with some covariates, or when we partial them out first.

R code

```
> #first, the more complicated model
> mod.glb <- setCor(govact ~ age * negemot + posemot + ideology + sex,
+                  data=globalWarm, std=FALSE)
> print(mod.glb, digits=3)
```

```
Call: setCor(y = govact ~ age * negemot + posemot + ideology + sex,
  data = globalWarm, std = FALSE)
```

Multiple Regression from raw data

```
DV = govact
```

	slope	se	t	p	lower.ci	upper.ci	VIF	Vy.x
(Intercept)	0.009	0.037	0.242	8.09e-01	-0.064	0.082	1.000	0.000
age	-0.001	0.002	-0.577	5.64e-01	-0.006	0.003	1.071	0.002
negemot	0.433	0.026	16.507	5.76e-53	0.382	0.485	1.172	0.281
posemot	-0.021	0.028	-0.768	4.43e-01	-0.076	0.033	1.029	-0.001
ideology	-0.212	0.027	-7.883	1.04e-14	-0.264	-0.159	1.199	0.098
sex	-0.011	0.076	-0.147	8.83e-01	-0.160	0.138	1.053	0.000
age*negemot	0.006	0.002	4.104	4.48e-05	0.003	0.009	1.015	0.020

Residual Standard Error = 1.057 with 808 degrees of freedom

```
Multiple Regression
```

	R	R2	Ruw	R2uw	Shrunken R2	SE of R2	overall F	df1	df2	p
govact	0.633	0.401	0.459	0.21	0.396	0.026	90.08	6	808	1.825e-86

R code

```
> # compare this to the partialled model
>
> mod.glb.partialled <- setCor(govact ~ age * negemot - posemot - ideology - sex, data = globalWarm)
>
```

Note how the beta weights for the age, negemot and interaction terms are identical.

6.2 Partial everything from everything

Sometimes we want to examine just the independent effects of all our variables. That is to say, we want to partial all the variables from all the other variables. I do this with the `partial.r` function. To show the results, I compare the partialled rs to the original rs. I

show the lower off diagonal matrix using `lowerMat`. Then to compare the partial matrix to the original matrix, I form the square matrix where the lower off diagonal is the original matrix and the upper off diagonal is the partial matrix.

```
> upper <- partial.r(globalWarm)
> lowerMat(upper) #show it
```

```
      govct posmt negmt idlgy age  sex  prtyd
govact    1.00
posemot  -0.03  1.00
negemot   0.50  0.13  1.00
ideology -0.19  0.00 -0.07  1.00
age       -0.02  0.04  0.03  0.14  1.00
sex        0.00  0.08 -0.07  0.04  0.14  1.00
partyid  -0.08 -0.01 -0.09  0.53  0.03  0.02  1.00
```

```
> lower <- lowerCor(globalWarm)
```

```
      govct posmt negmt idlgy age  sex  prtyd
govact    1.00
posemot   0.04  1.00
negemot   0.58  0.13  1.00
ideology -0.42 -0.03 -0.35  1.00
age       -0.10  0.04 -0.06  0.21  1.00
sex       -0.10  0.07 -0.12  0.13  0.17  1.00
partyid  -0.36 -0.04 -0.32  0.62  0.15  0.11  1.00
```

```
> lowup <- lowerUpper(lower, upper)
>
```

pdf
2

7 Related packages

`mediate` and `setCor` are just two functions in the *psych* package. There are several additional packages available in R to do mediation. The *mediation* package ([Tingley et al., 2014](#)) seems the most powerful, in that is tailor made for mediation. *MBESS* ([Kelley, 2017](#)) has a mediation function. Steven Short has a nice tutorial on mediation analysis available for download [that discusses how to use R for mediation](#). And, of course, the *lavaan* package ([Rosseel, 2012](#)) is the recommended package to do SEM and path models.




Figure 15: Correlations (below diagonal) and partial correlations (above the diagonal)

8 Development version and a users guide

The *psych* package is available from the CRAN repository. However, the most recent development version of the *psych* package is available as a source file at the repository maintained at <http://personality-project.org/r>. That version will have removed the most recently discovered bugs (but perhaps introduced other, yet to be discovered ones). To install this development version, either for PCs or Macs,

```
install.packages("psych", repos = "http://personality-project.org/r", type = "source")
```

After doing this, it is important to restart R to get the new package.

Although the individual help pages for the *psych* package are available as part of R and may be accessed directly (e.g. `?psych`), the full manual for the *psych* package is also available as a pdf at http://personality-project.org/r/psych_manual.pdf

News and a history of changes are available in the NEWS and CHANGES files in the source files. To view the most recent news,

```
> news (Version >= "2.0.12", package="psych")
```

9 Psychometric Theory

The *psych* package has been developed to help psychologists do basic research. Many of the functions were developed to supplement a book (<http://personality-project.org/r/book> An introduction to Psychometric Theory with Applications in R (Revelle, prep) More information about the use of some of the functions may be found in the book .

For more extensive discussion of the use of *psych* in particular and R in general, consult <http://personality-project.org/r/r.guide.html> A short guide to R.

10 SessionInfo

This document was prepared using the following settings.

```
> sessionInfo()
```

R version 4.1.2 (2021-11-01)
Platform: x86_64-apple-darwin17.0 (64-bit)
Running under: macOS Big Sur 10.16

Matrix products: default
BLAS: /Library/Frameworks/R.framework/Versions/4.1/Resources/lib/libRblas.0.dylib
LAPACK: /Library/Frameworks/R.framework/Versions/4.1/Resources/lib/libRlapack.dylib

```

locale:
[1] C

attached base packages:
[1] stats      graphics  grDevices  utils      datasets  methods   base

other attached packages:
[1] psychTools_2.2.1 psych_2.1.12

loaded via a namespace (and not attached):
 [1] compiler_4.1.2      parallel_4.1.2      tools_4.1.2         foreign_0.8-81      lavaan_0.6-7
 [8] mnormt_2.0.2        grid_4.1.2          pbivnorm_0.6.0      knitr_1.33          xfun_0.24
[15] lattice_0.20-45

```


References

- Cohen, J. (1982). Set correlation as a general multivariate data-analytic method. *Multivariate Behavioral Research*, 17(3):301–341.
- Cohen, J., Cohen, P., West, S. G., and Aiken, L. S. (2003). *Applied multiple regression/correlation analysis for the behavioral sciences*. L. Erlbaum Associates, Mahwah, N.J., 3rd ed edition.
- Dawes, R. M. (1979). The robust beauty of improper linear models in decision making. *American Psychologist*, 34(7):571–582.
- Garcia, D. M., Schmitt, M. T., Branscombe, N. R., and Ellemers, N. (2010). Women’s reactions to ingroup members who protest discriminatory treatment: The importance of beliefs about inequality and response appropriateness. *European Journal of Social Psychology*, 40(5):733–745.
- Hayes, A. F. (2013). *Introduction to mediation, moderation, and conditional process analysis: A regression-based approach*. Guilford Press, New York.
- Hotelling, H. (1936). Relations between two sets of variates. *Biometrika*, 28(3/4):321–377.
- Kelley, K. (2017). *MBESS: The MBESS R Package*. R package version 4.4.1.
- Pollack, J. M., Vanepps, E. M., and Hayes, A. F. (2012). The moderating role of social ties on entrepreneurs’ depressed affect and withdrawal intentions in response to economic stress. *Journal of Organizational Behavior*, 33(6):789–810.
- Preacher, K. J. (2015). Advances in mediation analysis: A survey and synthesis of new developments. *Annual Review of Psychology*, 66:825–852.
- Preacher, K. J. and Hayes, A. F. (2004). SPSS and SAS procedures for estimating indirect effects in simple mediation models. *Behavior Research Methods, Instruments, & Computers*, 36(4):717–731.
- Preacher, K. J., Rucker, D. D., and Hayes, A. F. (2007). Addressing moderated mediation hypotheses: Theory, methods, and prescriptions. *Multivariate behavioral research*, 42(1):185–227.
- R Core Team (2020). *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria.
- Revelle, W. (2020). *psych: Procedures for Personality and Psychological Research*. Northwestern University, Evanston, <https://CRAN.r-project.org/package=psych>. R package version 2.0.9.
- Revelle, W. (in prep). *An introduction to psychometric theory with applications in R*. Springer.

- Rosseel, Y. (2012). lavaan: An R package for structural equation modeling. *Journal of Statistical Software*, 48(2):1–36.
- Tal-Or, N., Cohen, J., Tsfati, Y., and Gunther, A. C. (2010). Testing causal direction in the influence of presumed media influence. *Communication Research*, 37(6):801–824.
- Tingley, D., Yamamoto, T., Hirose, K., Keele, L., and Imai, K. (2014). mediation: R package for causal mediation analysis. *Journal of Statistical Software*, 59(5):1–38.

References

- Cohen, J. (1982). Set correlation as a general multivariate data-analytic method. *Multivariate Behavioral Research*, 17(3):301–341.
- Cohen, J., Cohen, P., West, S. G., and Aiken, L. S. (2003). *Applied multiple regression/correlation analysis for the behavioral sciences*. L. Erlbaum Associates, Mahwah, N.J., 3rd ed edition.
- Dawes, R. M. (1979). The robust beauty of improper linear models in decision making. *American Psychologist*, 34(7):571–582.
- Garcia, D. M., Schmitt, M. T., Branscombe, N. R., and Ellemers, N. (2010). Women’s reactions to ingroup members who protest discriminatory treatment: The importance of beliefs about inequality and response appropriateness. *European Journal of Social Psychology*, 40(5):733–745.
- Hayes, A. F. (2013). *Introduction to mediation, moderation, and conditional process analysis: A regression-based approach*. Guilford Press, New York.
- Hotelling, H. (1936). Relations between two sets of variates. *Biometrika*, 28(3/4):321–377.
- Kelley, K. (2017). *MBESS: The MBESS R Package*. R package version 4.4.1.
- Pollack, J. M., Vanepps, E. M., and Hayes, A. F. (2012). The moderating role of social ties on entrepreneurs’ depressed affect and withdrawal intentions in response to economic stress. *Journal of Organizational Behavior*, 33(6):789–810.
- Preacher, K. J. (2015). Advances in mediation analysis: A survey and synthesis of new developments. *Annual Review of Psychology*, 66:825–852.
- Preacher, K. J. and Hayes, A. F. (2004). SPSS and SAS procedures for estimating indirect effects in simple mediation models. *Behavior Research Methods, Instruments, & Computers*, 36(4):717–731.
- Preacher, K. J., Rucker, D. D., and Hayes, A. F. (2007). Addressing moderated mediation hypotheses: Theory, methods, and prescriptions. *Multivariate behavioral research*, 42(1):185–227.

- R Core Team (2020). *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria.
- Keon-Woong Moon (2020). *processR: Implementation of the 'PROCESS' Macro*. <https://CRAN.R-project.org/package=processR>
- Revelle, W. (2020). *psych: Procedures for Personality and Psychological Research*. Northwestern University, Evanston, <https://CRAN.r-project.org/package=psych>. R package version 2.0.12.
- Revelle, W. (in prep). *An introduction to psychometric theory with applications in R*. Springer.
- Rosseel, Y. (2012). lavaan: An R package for structural equation modeling. *Journal of Statistical Software*, 48(2):1–36.
- Tal-Or, N., Cohen, J., Tsfaty, Y., and Gunther, A. C. (2010). Testing causal direction in the influence of presumed media influence. *Communication Research*, 37(6):801–824.
- Tingley, D., Yamamoto, T., Hirose, K., Keele, L., and Imai, K. (2014). mediation: R package for causal mediation analysis. *Journal of Statistical Software*, 59(5):1–38.